



Characteristics of RTD & Thermocouple

Model : SE-1038

SINCOM SE-1038 Characteristics of RTD and Thermocouple is a versatile and all-inclusive trainer designed for studying the characteristics of RTD (Resistance Temperature Detector) and Thermocouple. It offers the convenience of adjusting the DC supply voltage and includes on-board digital instruments such as a DC voltmeter, DC ammeter, and temperature indicator. Additionally, it features an electrical heating system for practical experimentation. This comprehensive trainer provides a complete learning experience for understanding the behaviour and properties of RTD and Thermocouple.

Features

- ❖ Platinum RTD and CRAL type Thermocouple
- ❖ Wide Temperature Range
- ❖ $3^{1/2}$ Digit LED Digital DC Volt and Current Indicator
- ❖ Digital Temperature Indicator
- ❖ External Electrical Heating System
- ❖ Current controlling resistor in series
- ❖ In-Built Fixed and Variable regulated DC Power Supply
- ❖ Presents a multi-color Circuit Diagram printed on the front panel of the white board
- ❖ Enclosed in an attractive, light weight, High Quality, Poly Coated Imported Pine Wooden cabinet
- ❖ Interconnections by 2mm high quality banana sockets and pins.

Technical Specifications

▪ AC Mains Power Supply	: 230V \pm 10%, 50Hz
▪ Fixed Regulated DC Power Supply	: +5V /500mA
▪ Variable DC Power Supply	: Variable 0 to +12V
▪ Temperature Sensor	: RTD PT 100 and CRAL K type Thermocouple
▪ Heating Source	: Electrical Heating system
▪ Temperature Range	: Upto 100° C
▪ Current Controlling Resistor	: MFR 100 Ω , \pm 5% in series
▪ Maximum Forward Current	: 100mA
▪ Maximum Output Voltage	: 12V
▪ Total Digital Meters	: 03 (1 Voltmeter, 1 Milliammeter and 1 Temperature)
▪ Digital Voltmeter	: DC 0-20V, Red Color $3^{1/2}$ Digit LED Display
▪ Digital Milliammeter	: DC 0-100mA, Red Color $3^{1/2}$ Digit LED Display
▪ Digital Temperature Indicator	: $3^{1/2}$ Digit LED Temperature Display upto 100°C with sensor
▪ Weight	: 3.0 kg (approx)
▪ Dimensions (mm)	: L 245 x W 320 x H 115
▪ Interconnections	: 2mm Banana sockets
▪ Operating Temperature	: 0-100°C, 80% RH



An ISO 9001:2015 Co.

Learning Scope

- **To study Construction of RTD.** To study the change in Resistance w.r.t. change in Temperature. To Observe and note the change in Voltage(V) and Current(I) of RTD w.r.t. change in Temperature. To Plot Temperature Vs Resistance characteristics.
- **To study Construction of Thermocouple.** To study thermocouple as an active transducer. To study Temperature Vs Voltage across Thermocouple characteristics. To Observe and note the change in Voltage (V) of RTD w.r.t. change in Temperature.

Other Instruments Required : Digital Multimeter

Accessories Included : Electrical Heating System, Digital Temperature Indicator with sensor, RTD, Thermocouple, Set of Patch Cords, Detail Instruction Manual.